TORNADO ACS
Advanced Cleaning System

Application table for granules

100% ECO FRIENDLY

	granules technical term grain size (mm)	in Top, Premium, Elite and Elite Plus - System					special granulate		engraving
		nutshell NS 450 0,2 - 0,45	**jet glass SG 150** 0,1 - 0,2	**jet glass SG 300** 0,2 - 0,3	**asilit AS 180** 0,04 - 0,18	**asilit AS 250** 0,09 - 0,25	**jet plast ® DP 200** 0,1 - 0,2	**jet plast ® DP 600** 0,3 - 0,6	**corundum EK 75** 0,045-0,075
natural stone	granite polished	6					5		3
	granite unpolished	6	5	6	5	6			3
	marble polished	6					5		3
	marble unpolished	6	5		5				3
	limestone		5		5				3
	sandstone		5		5				3
artificial stone	ceramic - glazed		5		5				
	ceramic - unglazed	6					5		
	brick - burnt		5	6	5	6			
	claytile - glazed	6					5		
	claytile - unglazed		5		5				
	lime sandstone		5						
	concrete		5	6	5	6			
	washed concrete		5		5				
plaster	EIFS		5						
	roughcast		5						
	coat of paint		5						
	plastic plaster	6							
metal	copper	6	4		4				3
	derust iron/steel			6		6			3
	aluminium	6	4		4				3
	bronze	6	4		4				3
	brass	6	4		4				3
	stainless steal	6	4		4			8	3
synthetic	advertising panel	6					5		
	advertising foil	6							
wood	softwood		5		4				
	hardwood		5	6	4				

dosage setting 2 = Ø 2 mm 3 = Ø 3 mm 4 = Ø 4 mm 5 = Ø 5 mm 6 = Ø 6 mm 8 = Ø 8 mm

This table shows general recommendations for the application of granulate. Due to the interactions between colours and base coat as well as fluctuations of quality, we cannot make any guarantees for this table.
The dosage setting is located in the lower container. Tips to change the dosage setting you can find on **page 10** of the operations manual.